

## Current Transformer Design Form

\* Contact Name: \_\_\_\_\_  
\* Company: \_\_\_\_\_  
\* Telephone: \_\_\_\_\_  
\* Email: \_\_\_\_\_  
Fax: \_\_\_\_\_  
Address: \_\_\_\_\_  
City: \_\_\_\_\_  
State: \_\_\_\_\_  
Zip Code: \_\_\_\_\_

Quotation Quantity: \_\_\_\_\_

### CT Specifications:

\* Input: \_\_\_\_\_ Amps  
\* Output: \_\_\_\_\_ Amps or \_\_\_\_\_ Volts  
\* Burden: \_\_\_\_\_ Ohms or \_\_\_\_\_ VA.  
\* Frequency: \_\_\_\_\_ Hz.

### \* Application and Accuracy Classification: ( Check one).

- Electronic  ± 1%  ± 3%  ± 5%  Other (Specify) \_\_\_\_\_  
 Metering. Accuracy Classification: \_\_\_\_\_  
 Relaying. Accuracy Classification: \_\_\_\_\_  
 Other (Specify) \_\_\_\_\_

### Dimensional Limits (Fill if applicable)

Min. Inside Diameter: \_\_\_\_\_ in.  
Max. Outside Diameter: \_\_\_\_\_ in.  
Max. Height: \_\_\_\_\_ in.

### \* Lead Type (Check One.):

- UL1015 Stranded Wire  
 Teflon Stranded Wire  
 PC Pin  
 Other (Specify): \_\_\_\_\_  
 \* Lead or Pin Length? \_\_\_\_\_

### \* Mounting Style: (Chose One):

- Cup Encapsulation  
 Full Epoxy Encapsulation  
 Fiberglass Tape and Varnish  
 Fiberglass Tape and Epoxy Dip  
 Other (Specify) \_\_\_\_\_

Hi-Pot: \_\_\_\_\_ Volts.

Comments: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Drawing/File: \_\_\_\_\_

^ Starred items are required information.